



The LS475A is an 'underwater candle', used to light the body of water or to backlight objects on the water's surface. The optional base provides for a full range of positioning to suit any application. Without the base, the luminaire can be located amongst rocks or other objects to give a less structured appearance of light.

SPECIFICATIONS




Lamp Source	Halogen Bi-pin (G4 / GY6.35)	100 W ⁽¹⁾
IP Rating	IP68	
Submersion Depth	1.5 m	
Construction	Nickel plated brass	
Installation Type	Surface mount	
Standard Inclusions	MicroAntiLeach™ cable entry Thermal cutout 5 m cable	
Ambient Operating Temperature	5 °C to 40 °C	
Warranty	3 year structural, 1 year electrical	
Accessories	LS679 Mounting plate <i>Order separately</i>	

NOTE: Product specifications are subject to change without notice. Any luminaire can become hot - take care with appropriate use and placement.

⁽¹⁾ Nominal power consumption only, actual power consumed may vary.



**LS475A with
LS679 Pond Monster Mounting Plate**
Order separately



**LS679 Pond Monster
Mounting Plate**
Order separately

CONFIGURE THIS PRODUCT >

LS475				A	
SOURCE				↑	
Lamp	Wattage	Base	Voltage	Code	
Halogen Bi-pin / QT12	100 W max	G4 / G6.35	12 V AC ⁽¹⁾	A	

⁽¹⁾ Requires remote transformer.